

# (12) UK Patent Application (19) GB (11) 2 397 687 (13) A

(43) Date of A Publication 28.07.2004

(21) Application No: 0401496.5

(22) Date of Filing: 23.01.2004

(30) Priority Data:  
(31) 0301700 (32) 24.01.2003 (33) GB

(71) Applicant(s):  
Macrovision Europe Limited  
(Incorporated in the United Kingdom)  
Woodley House, Crockhamwell Road,  
Woodley, READING, Berkshire, RG5 3JP,  
United Kingdom

(72) Inventor(s):  
Philippe Marcel Henri Selve  
Victor Kovner  
Richard A. A. Heylen

(74) Agent and/or Address for Service:  
W. H. Beck, Greener & Co  
7 Stone Buildings, Lincoln's Inn, LONDON,  
WC2A 3SZ, United Kingdom

(51) INT CL<sup>7</sup>:  
G11B 20/00

(52) UK CL (Edition W):  
G5R RB265 RHB

(56) Documents Cited:  
GB 2369718 A EP 0918326 A1  
EP 0791923 A2 JP 2002175662 A

(58) Field of Search:  
UK CL (Edition W) G5R  
INT CL<sup>7</sup> G11B  
Other: Online: WPI; EPODOC; JAPIO; INSPEC;  
INTERNET

BEST AVAILABLE COPY

(54) Abstract Title: **The copy protection of optical discs**

(57) The present invention relates to a method of copy protecting optical discs, such as CD-ROMs. Instead of encoding data onto the CD-ROMs in a manner which ensures balanced dc content, for copy protection the digital data is encoded and recorded onto the optical disc such that it is arranged to give some of the recorded digital data unbalanced dc content. Thus, for example, the DSV value of the encoded data may be changed rapidly in less than 100 frames (Figure 9). For an area of digital data on the optical disc in which the DSV has been caused to rise steeply (Figure 10a), heavy distortions in audio arise (Figure 10c) during an attempt to copy an audio track including the single segment of unbalanced dc content.




FIG. 9

GB 2 397 687 A




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 11

10A



10B




FIG. 10



10C




FIG. 10 CONT'D

## THE COPY PROTECTION OF OPTICAL DISCS

The present invention relates to a method of copy protecting optical discs, to optical discs when so copy protected, and to a data file for enabling digital data to be recorded in an encoded and copy protected form on an optical disc.

Optical discs, such as the various formats of compact discs (CDs) and of digital versatile discs (DVDs) are increasingly used for carrying information for many different applications. The information encoded onto the optical discs is generally very valuable and accordingly, they are increasingly copied by counterfeiters. Furthermore, recordable CDs, and CD writers for writing the information content from one disc to such recordable discs, are now readily available to the domestic consumer. Recordable DVDs and DVD writers are expected to become as readily available in the short term. This means that new and effective methods for copy protecting optical discs are required.

The present invention seeks to provide new methods of copy protection.

According to a first aspect of the present invention there is provided a method of copy protecting an optical disc comprising the step of encoding and recording digital data onto the optical disc in a manner which is arranged to give some of the recorded digital data unbalanced dc content.

Preferably, the unbalanced dc content is given to selected areas of the recorded digital data on the disc.

In the main, players of the information on an optical disc can play the information recorded thereon despite the unbalanced dc content. However, readers of the information will experience difficulties in accessing the information, and, for example, may be caused to jitter. The unbalanced dc content causes graver problems when attempts are made to copy extracted data by known "ripping" techniques.

In this respect, in this specification the term "player" is used to refer to players and drives arranged or controlled to play the data on an optical disc. This might be, for example, the audio data on a digital audio compact disc

(CD-DA), or the video data on a digital versatile disc (DVD). Such players will include, therefore, commercially available CD music players which function solely to play the music or other audio on the CD, and commercially available DVD players which function solely to play the films or other video on the DVD. It is generally required that the copy protection methods of the invention do not generally impinge on the normal operation of such "players".

In this specification the term "data reader" is used to refer to all players and drives arranged or controlled to read the data on the optical disc, for example, by extracting or ripping the data from the disc. Such players will include, therefore, CD-ROM and CD-I drives when configured or controlled to read or extract audio data from a CD. In this respect, it is required to enable drives to play legitimate optical discs, but to prevent them from being used to extract the data from the discs or to make usable copies of the discs.

In an embodiment, methods of the invention further comprise predetermining the selected areas of the recorded digital data which are to be given unbalanced dc content.

Where the selected areas are predetermined, methods of the invention may also act to provide for authentication of genuine discs and/or to provide signatures for discs. In this respect, to establish if a disc is genuine or if a signature has been provided, it is necessary only to look to the predetermined selected areas to see if they contain unbalanced dc content.

In an alternative method of the invention, the method further comprises randomly selecting the selected areas of the recorded digital data which are to be given unbalanced dc content.

In an embodiment, the method may further comprise recording the digital data onto the optical disc in frames, and providing that each selected area having unbalanced dc content contains less than 100 frames.

The method may comprise recording the digital data onto the optical disc in frames arranged into sectors each having a plurality of frames, and providing that each selected area having unbalanced dc content contains less than 2 sectors.

For example, each sector contains 98 frames.

5 The selected areas which are given unbalanced dc content are preferably restricted in size such that a player can treat the tracking errors caused thereby as burst errors. In this situation, therefore, a player will generally be able to continue playing information from the disc without degradation.

10 In an embodiment, the method further comprises giving some of the recorded digital data unbalanced dc content by providing the recorded digital data with poor DSV characteristics.

For example, the DSV of the recorded digital data may have a rapid rate of change.

15 Additionally and/or alternatively, the DSV of the recorded digital data may have high absolute values.

20 Additionally and/or alternatively, the DSV of the recorded digital data may have substantial low frequency components.

25 Preferably, the recorded digital data on the optical disc is given unbalanced dc content by encoding selected areas of the digital data to have poor DSV characteristics.

According to a further aspect of the invention, there is provided a copy protected optical disc having encoded digital data recorded thereon, and wherein some of the digital data recorded on the optical disc has unbalanced dc content.

30 In an embodiment of a copy protected optical disc of the invention, selected areas of the recorded digital data on the optical disc have unbalanced dc content.

35 In one embodiment, selected areas of the recorded digital data which have unbalanced dc content have been predetermined.

In an alternative embodiment, selected areas of the recorded digital data which have unbalanced dc content have been randomly selected.

Preferably, the size of each said selected area is restricted.

5

Where the digital data recorded onto the optical disc has been arranged in frames, each said selected area having unbalanced dc content may contain less than 100 frames.

10

Where the digital data recorded onto the optical disc has been arranged in sectors with each sector containing a plurality of frames, each said selected area having unbalanced dc content may contain less than 2 sectors. Preferably, each sector contains 98 frames.

15

In a preferred embodiment, some of the digital data recorded on the optical disc has been given unbalanced dc content by providing the recorded digital data with poor DSV characteristics.

For example, the DSV of the recorded digital data may have a rapid rate of change, and/or high absolute values, and/or substantial low frequency components.

The present invention is relevant to all formats of optical discs, for example, the optical disc may be a CD which has been subjected to EFM encoding, or the optical disc may be a DVD which has been subjected to EFMPlus encoding.

Similarly, the invention is applicable irrespective of the type of information carried by the optical disc. For example, the digital data recorded on the optical disc may be one or more of: audio data, video data, graphics data, visual data, animation data, numerical data, program data, control and access data, and/or any other data.

The invention also extends to a data file enabling digital data to be encoded and copy protected by a method as defined above.

35

Such a data file may be arranged to be executable.

The present invention also extends to a data file for enabling digital data to be recorded in an encoded and copy protected form on an optical disc, the data file having an algorithm for enabling the selection of digital data to be specially encoded, and then for enabling encoding of the selected digital data such that it has unbalanced dc content.

A data file of the invention, which may or may not be an executable file, is intended for use by an encoder for the optical disc. For example, the data file may be utilised by the encoder of a laser beam recorder during mastering of an optical disc.

The encoder is enabled or controlled by the algorithm to select areas of the digital data for special encoding, and it is this special encoding which adds the unbalanced dc content to the master disc.

Where the digital data is to be encoded using EFM encoding with merge bits chosen during encoding inserted between successive channel bits, the data file algorithm enables merge bits to be chosen to give poor DSV characteristics to the selected digital data.

Where the digital data is to be encoded using EFMPlus encoding where each 8 bit data word is encoded into one of a choice of four 16 bit channel words, the data file algorithm enables 16 bit channel words to be chosen to give poor DSV characteristics to the selected digital data.

In an embodiment, the algorithm enables selected areas of the digital data to be chosen for special encoding, each selected area being restricted in size.

For example, the algorithm determines the number of frames to be contained within one said selected area of the digital data.

One said selected area may have less than 100 frames.

In an embodiment, the algorithm determines the encoding for each said selected area of the digital data which would provide good DSV characteristics, compares the good DSV value with a predetermined DSV value, and then

changes the encoding for each said selected area such that the DSV value approaches the predetermined value whereby poor DSV characteristics are given to each said selected area.

5           Embodiments of the present invention will hereinafter be described, by way of example, with reference to the accompanying drawings, in which:

          Figure 1 shows an enlarged view of a CD showing the pits and lands,

          Figure 2 shows a section through a pit and land illustrating the data encoding thereof,

10          Figure 3 illustrates the DSV corresponding to the encoded data,

          Figure 4 shows schematically the manner in which merge bits can be chosen,

          Figure 5 shows schematically the encoding of data onto a CD,

          Figure 6 illustrates a frame in the encoded data,

15          Figure 7 illustrates EFMPlus encoding,

          Figure 8 shows schematically part of a spiral track on an optical disc and its tracking,

          Figure 9 illustrates poor DSV characteristics to be encoded onto a disc,

20          Figure 10 illustrates the effect of poor DSV characteristics, with Figure 10a showing the DSV characteristic, Figure 10b showing the associated dc content, and Figure 10c showing the distortions in audio produced thereby, and Figure 11 graphically illustrates the encoding algorithm.

          This description specifically explains the encoding of a CD-ROM and the use of the present invention for copy protecting such a CD-ROM. However, it will be appreciated that the present invention is not limited to use with a CD-ROM and finds application to all data carrying optical discs. Specifically, the invention is applicable to all formats of CDs and to all formats of DVDs.

30          Furthermore, the description which follows gives one example of the encoding of data onto a CD. Other encoding modes are possible and it will be appreciated that the invention is not limited to the encoding mode.

          Figure 1 shows an enlarged view of part of a CD showing the pits 6 thereon. As is well known, these pits extend along a spiral track on the surface of the disc and are separated by lands.

Figure 2 shows a section through a pit 6 and land 8 illustrating how data is encoded on a CD. The pits and lands do not represent binary 0s and 1s, but instead represent transitions from one state to another. The data signal is stored in NRZI form (Non-Return to Zero Inverted), where the signal is inverted every time a 1 is encountered. Figure 2 shows the binary value 00100010.

The data stream always consists of pits and lands of at least 3 bits and at most 11 bits long. This is sometimes referred to as a 3T-11T where T is a 1 bit period. A 3T pit has the highest signal frequency (720khz) and an 11T pit has the lowest signal frequency (196khz).

A data signal is derived from the lengths of the pits and lands. The produced signal forms a square wave known as an EFM signal. The digital sum value (DSV) is the running difference between the number of T values where the EFM represents a pit and the number of T values where the EFM represents a land. As each data bit is read, the DSV is incremented or decremented depending upon whether the data bit corresponds to a pit or a land.

As indicated in Figure 3, the DSV is determined by assigning the value +1 to each land T, and -1 to each pit T. Ideally, the DSV should stray as little as possible from the zero level. If the DSV has a rapid rate of change over a significant period of time or if the DSV has substantial low frequency components then the transitions in the EFM signal may be shifted from their ideal values and/or the ability of tracking and focus circuits in CD players or drives to maintain optimal head positioning may be compromised. This typically causes read failures from the CD. This is discussed further below.

Original data, in 8 bit bytes, is passed through a process called EFM encoding to produce the 14 bit symbols, often referred to as channel bits. The set of 14 bit symbols is especially designed:

- to level out the number of pits and lands, to help maintain balanced DSV;
- and
- to ensure that there are no symbols which break the EFM coding scheme of 3T-11T.

Another way of regarding the 3T-11T run length limiting rules is that the number of successive zeros must be greater than two and less than ten. It is



immediately apparent that this requirement may be compromised where two 14 bit symbols follow one after the other. Accordingly, a set of 3 merge bits are added between each 14 bit symbol and the one following to ensure that there are no violations of the 3T-11T coding scheme and to ensure that a suitable  
 5 DSV is maintained.

Figure 4 shows schematically the manner in which the merge bits can be chosen. In Figure 4 there are shown two 8 bit data symbols 30. These are encoded into two 14 bit channel words 32, for example, by reference to a look  
 10 up table. Then, to ensure that the resultant merged symbols 32 meet the run length limiting rules, three merge bits XMM are inserted between successive channel symbols 32.

In the example illustrated in Figure 4, three combinations of merge bits  
 15 XMM are possible. Figure 4 shows the transitions for the merged words for each choice of the merge bits XMM and also shows the DSV associated with each choice. In the embodiment illustrated, the merge bits 000 give a DSV value of -1, the merge bits 010 give a DSV value of +7, and the merge bits 001 give a DSV equal to +6. In most cases, therefore, the encoder will choose the  
 20 merge bits 000 to give the lowest absolute DSV value.

Figure 5 shows schematically the encoding of data onto a CD in the form of pits 6 and lands 8. Initially, and as indicated, there are 2048 bytes of user data. This is indicated at 10. Then, as illustrated at 12, a sync block, a header,  
 25 an error detection code (EDC) 14 and error correction code (ECC) 16 are added to those original 2048 bytes.

To help ensure that the final arrangement of pits and lands meet the EFM coding rules for DSV, the data at 12 is then scrambled as shown at 18 using an  
 30 XOR algorithm. The scrambling seeks to reduce the likelihood that plausible repeating patterns of user data would inadvertently correspond to DSV problem causing patterns by effectively randomising the data across a sector.

As indicated at 20, the data is then passed to the CIRC encoder. The  
 35 CIRC encoder, by means of delays, distributes the data across a number of sectors. The data is then passed to the EFM encoder 22 where the 8 bit data words are translated into the 14 bit channel words and the merge bits are

inserted to form the pattern of 1's and 0's. It is the EFM encoded data which is converted into the series of pits and lands on the disc.

As is also known, the encoded data on a CD is arranged in frames. The format of a frame is illustrated in Figure 6 which shows that each frame has sync data, sub-code bits providing control and display symbols, and parity bits together with data bits. Each frame includes 24 bytes of data, which, for a CD-DA, for example, is audio data.

There are 8 sub-code bits contained in every frame and designated as P, Q, R, S, T, U, V and W. Generally only the P and Q sub-code bits are used in the audio format. The standard requires that 98 of the frames of Figure 6 are grouped into a sector, and the sub-code bits from the 98 frames are collected to form sub-code blocks. That is, each sub-code block is constructed a byte at a time from 98 successive frames. In this way, 8 different subchannels, P to W, are formed. These subchannels contain control data for the disc. The P- and Q- subchannels incorporate timing and navigation data for the tracks on the disc.

The data encoding on a CD-DA and on a CD-ROM, which is briefly described above, is well known and in accordance with international standards. Accordingly, it is not necessary to further describe the encoding, nor the rules to which it complies, as both are well known and understood to those skilled in the art.

Similarly, the encoding schemes and compliance rules for DVDs are well known and will not be described in detail herein. In this respect, DVDs do not use an EFM encoding scheme with merge bits as described above. DVDs use an encoding scheme known as EFMPlus which is schematically illustrated in Figure 7. In EFMPlus, the 8 bit data words indicated at 30 are translated into 16 bit channel words, indicated at 32, by way of the EFMPlus modulator 34. This EFMPlus modulator 34 incorporates a number of look up tables which provide a choice of four 16 bit words 32' for each input 8 bit word 30'. The algorithm controlling the modulator 34 manipulates the choice of the 16 bit words 32' to minimise and control DSV.

As set out above, one of the reasons for wishing to keep good DSV characteristics is that poor DSV characteristics can provide tracking problems, for example, in disc readers and players. In this respect, the DSV represents the dc content of the data signal derived from the pits and lands on the disc. If  
5 that output data signal has a dc offset, tracking problems can occur.

Figure 8 shows schematically part of a spiral track 40 on the surface of an optical disc and shows a number of pits 6 therein. The pits and lands are to be read by one or more lasers (not shown) which have a beam, as 42, which is  
10 focused on the track 40. A servo motor is required to maintain precise alignment between the laser beam 42 and the track 40, and between the laser beam 42 and the transition boundaries between the pit and land areas. If the data signal does not have a proper balance of high and low dc, such that the overall dc content is zero, there is the risk that the servo motor will drift out of  
15 proper alignment with the track 40.

Disc readers and players are provided with appropriate tracking systems (not shown) to keep the laser beam 42 centred on the track 40. As it plays a CD-DA, for example, the tracking system has to continually move the laser  
20 outwardly from the centre of the disc towards its periphery. As the laser moves outwardly the pits 6 move past the laser beam 42 at an increased and increasing speed. It will be appreciated that this speed increase occurs because the tangential speed of the pits is equal to the radius multiplied by the speed at which the disc revolves. Therefore, as the laser moves outwardly, the spindle  
25 motor (not shown) which rotates the disc must slow the speed of the optical disc. In this way it is ensured that the pits travel past the laser beam at a constant speed and that the data is read from the disc at a constant rate.

It is because the laser tracks the spiral of data using the pits that there  
30 cannot be extended gaps where there are no pits in the data track. This leads to the run length limiting rules described above.

Thus, it is generally required to encode data onto a disc such that the DSV does not have high absolute values, does not change rapidly, and does not  
35 have low frequency components. This latter requirement means that the DSV does not oscillate in a regular fashion. All these requirements ensure balanced dc content. As set out above, a balanced dc content helps the tracking system

of a reader or player to keep the laser beam centred on the track during data read out.

5 The applicants now, radically, suggest that digital data recorded on an optical disc should be given an unbalanced dc content, and that the unbalanced dc content created can be used to provide copy protection for optical discs.

10 In this respect, and as shown in Figure 9, in one embodiment the DSV value of the encoded data is changed rapidly in less than 100 frames. In the example shown in Figure 9, in less than 100 frames the DSV is changed from 0 to 3000 and then back again to 0. It is thought that where the dc content is unbalanced for less than two sectors, the run length limiting rules are not compromised so that no timing violations are introduced. It is also thought that the value of the DSV can be increased up to 10000 without any such violations  
15 occurring.

As discussed above, the existence of unbalanced dc content would generally force the servo motor of a player or reader to move out of proper alignment with the spiral track. However, because the unbalanced dc content is  
20 introduced in selected areas which are restricted in size, the unbalanced dc content appears to a player or reader as burst errors and is generally well handled by players. In this respect, audio and video players traditionally play at a speed of 1x, which equals a data transfer rate of 176.4 kbytes per second. Data readers, which may read at a speed of 50x and greater, are much more  
25 susceptible to the existence of unbalanced dc content. A data reader accessing the copy protected data may experience error messages, data errors and/or jitter.

However, it is software provided for the purpose of copying or ripping  
30 content from optical discs which is the most susceptible to the unbalanced dc content. Traditional ripping software, which uses buffering technology to retrieve data from a disc, reads the data in a sector for input into a first buffer, and then reads the data again in the same sector for input into a second buffer. The software requires the contents of the two buffers to be the same as a check that  
35 the data extracted is correct. The loss of tracking caused by the unbalanced dc content makes it difficult, as set out above, to reliably extract the data at all. However, it is even more difficult for the software to access the same position on

two separate occasions and to retrieve the same data therefrom. It is expected that such ripping techniques will fail to retrieve the data. Thus, the unbalanced dc content acts to copy protect the information stored on the disc.

5        Figure 10 illustrates the problems which a data reader will have when it tries to read data from an optical disc protected by a method of the invention. In Figure 10a there is shown an area of digital data on the optical disc in which the DSV has been caused to rise steeply over a limited number of frames. In this illustration, for example, the DSV rises to 4000 over 53 frames. Figure 10b  
10        shows the modified dc content associated with the same area of the disc, whilst Figure 10c shows heavy distortions in audio arising during an attempt to copy an audio track which has the single segment of unbalanced dc content as illustrated in Figure 10a.

15        The size, nature and frequency of occurrence of the areas of unbalanced dc content applied to an optical disc can be chosen as required. Currently it is proposed to introduce unbalanced dc content in the form of rapidly increasing DSV or as an oscillating DSV pattern. The unbalanced dc content may be applied to the optical disc alone or in addition to other copy protection or  
20        identification techniques.

      The unbalanced dc content may also be used in an authentication or signature technique. In this respect, it will be known where the unbalanced content has been located on a disc. A disc can then be checked to ensure that  
25        there is unbalanced data content at a particular location either to authenticate a disc or to control its use.

      Furthermore, it is possible to apply the unbalanced dc content to localised areas only of an optical disc to protect data in those localised areas from  
30        access.

      As set out above, for a CD the value of the merge bits is chosen by the encoder, for example, of a laser beam recorder, to minimise the DSV on a master disc. One method of adding unbalanced dc content to an optical disc,  
35        therefore, is to require the encoder to introduce a specific combination of merge bits at particular locations on the optical disc during mastering. This can be done, for example, by the following encoding algorithm:

1. Determine the length in frames of the segment where unbalanced dc content will be created.
2. Determine the desired DSV pattern by creating a one-dimensional vector which stores the values of DSV required after each frame in the segment. The length of this vector is equal to the number of frames in the segment.
3. For each frame in the segment:
  - 3.1 For each EFM symbol in the frame (14 channel bits):
    - 3.1.1. Read the following EFM symbol.
    - 3.1.2. Determine the legal combinations of merge bits between current and following EFM symbols.
    - 3.1.3. For each legal combination of merge bits:
      - 3.1.3.1. Calculate the DSV value which occurs after the following EFM symbol.
      - 3.1.3.2. Calculate the difference between the desired DSV value predetermined for the particular frame and that calculated in 3.1.3.1.
    - 3.1.4. Choose the combination of merge bits which minimises the value calculated in 3.1.3.2.
    - 3.1.5. If more than one such combination of merge bits exists, choose one that results in an EFM signal transition (pit-land, or land-pit).
  - 3.2 Encode the frame using the merge bit combinations calculated in 3.1.

This algorithm is shown graphically in Figure 11 in which the DSV pattern desired for a sequence of frames is indicated. As shown, the DSV is caused to increase at a rapid rate. The DSV at the end of one frame would be 250 or lower under normal encoding but, by way of the algorithm is brought to be as near to 500 as possible. This process carries on with successive frames such that the desired DSV profile is achieved.

It will be appreciated that variations in and amendments to the embodiments as described may be made within the scope of this application as defined in the accompanying claims.

**CLAIMS**

1. A method of copy protecting an optical disc comprising the step of encoding and recording digital data onto the optical disc in a manner which is arranged to give some of the recorded digital data unbalanced dc content.
2. A method of copy protecting an optical disc as claimed in Claim 1, further comprising giving unbalanced dc content to selected areas of the recorded digital data on the disc.
3. A method of copy protecting an optical disc as claimed in Claim 2, further comprising predetermining the selected areas of the recorded digital data which are to be given unbalanced dc content.
4. A method of copy protecting an optical disc as claimed in Claim 2, further comprising randomly selecting selected areas of the recorded digital data which are to be given unbalanced dc content.
5. A method of copy protecting an optical disc as claimed in any of Claims 2 to 4, further comprising restricting the size of each said selected area of the recorded digital data.
6. A method of copy protecting an optical disc as claimed in Claim 5, further comprising recording the digital data onto the optical disc in frames, and providing that each selected area having unbalanced dc content contains less than 100 frames.
7. A method of copy protecting an optical disc as claimed in Claim 5, further comprising recording the digital data onto the optical disc in frames arranged into sectors each having a plurality of frames, and providing that each selected area having unbalanced dc content contains less than 2 sectors.
8. A method of copy protecting an optical disc as claimed in Claim 7, wherein each sector contains 98 frames.

9. A method of copy protecting an optical disc as claimed in any preceding claim, further comprising giving some of the recorded digital data unbalanced dc content by providing the recorded digital data with poor DSV characteristics.
- 5 10. A method of copy protecting an optical disc as claimed in Claim 9, wherein the DSV of the recorded digital data has a rapid rate of change.
11. A method of copy protecting an optical disc as claimed in Claim 9 or Claim 10, wherein the DSV of the recorded digital data has high absolute  
10 values.
12. A method of copy protecting an optical disc as claimed in any of Claims 9 to 11, wherein the DSV of the recorded digital data has substantial low frequency components.
- 15 13. A method of copy protecting an optical disc as claimed in any preceding claim, wherein the recorded digital data on the optical disc is given unbalanced dc content by encoding selected areas of the digital data to have poor DSV characteristics.
- 20 14. A copy protected optical disc having encoded digital data recorded thereon, wherein some of the digital data recorded on the optical disc has unbalanced dc content.
- 25 15. A copy protected optical disc as claimed in Claim 14, wherein selected areas of the recorded digital data on the optical disc have unbalanced dc content.
16. A copy protected optical disc as claimed in Claim 15, wherein the  
30 selected areas of the recorded digital data which have unbalanced dc content have been predetermined.
17. A copy protected optical disc as claimed in Claim 15, wherein the  
35 selected areas of the recorded digital data which have unbalanced dc content have been randomly selected.



18. A copy protected optical disc as claimed in any of Claims 15 to 17, wherein the size of each said selected area is restricted.
19. A copy protected optical disc as claimed in Claim 18, wherein the digital  
5 data recorded onto the optical disc has been arranged in frames, and wherein each said selected area having unbalanced dc content contains less than 100 frames.
20. A copy protected optical disc as claimed in Claim 18, wherein the digital  
10 data recorded onto the optical disc has been arranged into sectors with each sector containing a plurality of frames, and wherein each said selected area having unbalanced dc content contains less than 2 sectors.
21. A copy protected optical disc as claimed in Claim 20, wherein each sector  
15 contains 98 frames.
22. A copy protected optical disc as claimed in any of Claims 14 to 21, wherein some of the digital data recorded on the optical disc has been given unbalanced dc content by providing the recorded digital data with poor DSV  
20 characteristics.
23. A copy protected optical disc as claimed in Claim 22, wherein the DSV of the recorded digital data has a rapid rate of change.
24. A copy protected optical disc as claimed in Claim 22 or Claim 23, wherein  
25 the DSV of the recorded digital data has high absolute values.
25. A copy protected optical disc as claimed in any of Claims 22 to 24, wherein the DSV of the recorded digital data has substantial low frequency  
30 components.
26. A copy protected optical disc as claimed in any of Claims 14 to 25, wherein the optical disc is a CD and has been subjected to EFM encoding.
27. A copy protected optical disc as claimed in any of Claims 14 to 25,  
35 wherein the optical disc is a DVD and has been subjected to EFMPlus encoding.

28. A copy protected optical disc as claimed in any of Claims 14 to 27, wherein the digital data recorded on the optical disc is one or more of: audio data, video data, graphics data, visual data, animation data, numerical data, program data, control and access data, and/or any other data.

5

29. A data file enabling digital data to be encoded and copy protected by a method as claimed in any of Claims 1 to 13.

30. A data file as claimed in Claim 29, which is arranged to be executable.

10

31. A data file for enabling digital data to be recorded in an encoded and copy protected form on an optical disc, the data file having an algorithm for enabling the selection of digital data to be specially encoded, and then for enabling encoding of the selected digital data such that it has unbalanced dc content.

15

32. A data file as claimed in Claim 31, wherein the digital data is to be encoded using EFM encoding where merge bits chosen during encoding are inserted between successive channel bits, and wherein the data file algorithm enables merge bits to be chosen to give poor DSV characteristics to the selected digital data.

20

33. A data file as claimed in Claim 31, wherein the digital data is to be encoded using EFMPlus encoding where each 8 bit data word is encoded into one of a choice of four 16 bit channel words, and wherein the data file algorithm enables the 16 bit channel words to be chosen to give poor DSV characteristics to the selected digital data.

25

34. A data file as claimed in any of Claims 31 to 33, wherein the algorithm enables selected areas of the digital data to be chosen for special encoding, each selected area being restricted in size.

30

35. A data file as claimed in Claim 34, wherein the algorithm determines the number of frames to be contained within one said selected area of the digital data.

35

36. A data file as claimed in Claim 35, wherein one said selected area has less than 100 frames.

37. A data file as claimed in any of Claims 34 to 36, wherein the algorithm determines the encoding for each said selected area of the digital data which would provide good DSV characteristics, compares the good DSV value with a  
5 predetermined DSV value, and then changes the encoding for each said selected area such that the DSV value approaches the predetermined value whereby poor DSV characteristics are given to each said selected area.

38. A data file as claimed in any of Claims 31 to 37, which is arranged to be  
10 executable.

39. A method of copy protecting an optical disc substantially as hereinbefore described with reference to the accompanying drawings.

15 40. A copy protected optical disc having encoded digital data recorded thereon, substantially as hereinbefore described with reference to the accompanying drawings.

20 41. A data file for enabling digital data to be recorded in an encoded and copy protected form on an optical disc, substantially as hereinbefore described with reference to the accompanying drawings.



Application No: GB 0401496.5  
Claims searched: All

Examiner: Donal Grace  
Date of search: 30 March 2004

## Patents Act 1977 : Search Report under Section 17

### Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance
X	1, 14 and 31 at least	GB 2369718 A (MACROVISION)
X	1, 14 and 31 at least	EP 0918326 A1 (HEWLETT-PACKARD)
X	1, 14 and 31 at least	EP 0791923 A2 (HEWLETT-PACKARD)
X	1, 14 and 31 at least	JP 2002175662 A (TOSHIBA EMI) see WPI abstract accession no 2002-524997

### Categories:

X Document indicating lack of novelty or inventive step	A Document indicating technological background and/or state of the art.
Y Document indicating lack of inventive step if combined with one or more other documents of same category.	P Document published on or after the declared priority date but before the filing date of this invention.
& Member of the same patent family	E Patent document published on or after, but with priority date earlier than, the filing date of this application

### Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC<sup>w</sup>:

G5R

Worldwide search of patent documents classified in the following areas of the IPC<sup>7</sup>:

G11B

The following online and other databases have been used in the preparation of this search report:

Online: WPI; EPODOC; JAPIO; INSPEC; INTERNET

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**